



PCR

Passive fiber optical network components for communication services

Version 1.3

March 2025

Changes made:

13 February 2024	text changes to installation scenario, clarification that amount of excess soil transportation is calculated per kilometer of cable.
5 October 2024	clarified in section 6.2.2 that the second paragraph is an informative indication and not a normative requirement
25 February 2025	Several textual changes from the 3 rd party review for the Nationale Environmental database

CONTENTS

INTRODUCTION	4
1 SCOPE	5
2 NORMATIVE REFERENCES.....	5
3 TERMS AND DEFINITIONS	5
4 ABBREVIATIONS.....	5
5 GENERAL ASPECTS	6
5.1 Objective of this general PCR for optical fiber products for communication services	6
5.2 Types of EPD with respect to life cycle stages covered	6
5.3 Comparability of EPD for construction products.....	6
5.4 Additional information	6
5.5 Ownership, responsibility and liability for the EPD	6
5.6 Communication format	6
6 PRODUCT CATEGORY RULES FOR LCA.....	7
6.1 Product category.....	7
6.2 Life cycle stages and their information modules to be included	7
6.2.1 General.....	7
6.2.2 A1-A3, Production stage	7
6.2.3 A4-A5, Construction process stage	7
6.2.4 B1-B5, use stage	8
6.2.5 B6-B7, use stage, related to the operation of the building	8
6.2.6 C1-C4, End-of-life stage.....	9
6.2.7 D, Benefits and loads beyond the system boundary	9
6.3 Calculation rules for the LCA	9
6.3.1 Functional or declared unit	9
6.3.2 Functional unit	9
6.3.3 Declared unit.....	10
6.3.4 Reference Service Life (RSL)	10
6.3.5 System boundaries.....	10
6.3.6 Criteria for the exclusion of inputs and outputs.....	10
6.3.7 Selection of data	10
6.3.8 Data quality	10
6.3.9 Developing product level scenarios.....	10
6.3.10 Units	10
6.4 Inventory Analysis	11
6.4.1 Data collection	11

6.4.2	Calculation procedures.....	11
6.4.3	Allocation of input flows and output emissions	11
6.5	Impact assessment	11
6.6	Interpretation.....	11
7	CONTENT OF THE EPD.....	11
7.1	Declaration of general information.....	11
7.2	Declaration of environmental parameters derived from LCA	11
7.2.1	General.....	11
7.2.2	Rules for declaring LCA information per module.....	11
7.2.3	Indicators describing environmental impacts based on LCA Assessment	12
7.2.4	Indicators describing resource use and environmental information based on Life Cycle Inventory (LCI).....	12
7.2.5	Information on biogenic carbon content	12
7.3	Scenarios and additional technical information	12
7.3.1	General.....	12
7.3.2	Construction process stage	12
7.3.3	B1-B7 use stage.....	12
7.3.4	End-of-life	12
7.4	Additional information on release of dangerous substances to indoor air, soil and water during the use stage	12
7.4.1	Indoor air.....	12
7.4.2	Soil and water	13
7.5	Aggregation of information modules	13
8	PROJECT REPORT.....	13
8.1	General	13
8.2	LCA related elements	13
8.3	Documentation and additional information	13
8.4	Data availability for verification	13
9	VERIFICATION AND VALIDITY OF AN EPD.....	13
10	BIBLIOGRAPHY	13

Introduction

This document provides Product Category Rules (PCR) for Environmental Product Declarations (EPD) for **passive fiber optical network components for communication services**. It complements the core product category rules for all construction products and services as established in EN 15804 and the Dutch horizontal PCR for construction products “Bepalingsmethode milieuprestatie bouwwerken 1.1”¹.

European Standard EN 15804 provides core product category rules for all construction products and services. It provides a structure to ensure that all Environmental Product Declarations (EPD) of construction products, construction services and construction processes are derived, verified and presented in a harmonized way.

An EPD communicates verifiable, accurate, non-misleading environmental information for products and their applications, thereby supporting scientifically based, fair choices and stimulating the potential for market-driven continuous environmental improvement.

This PCR was developed from June 2021 to may 2023, by a Dutch PCR work group within NLconnect, with representatives from the fiber optical industry.

Members of the PCR working group:

Amadys (Netceed)	Patty	van	Broekhoven
Attema	Michel		Schwarz
BAM Telecom	Jaap	de	Water
Circet	Peter		Zijderveld
Compose/Legrand	Huug	van der	Meeren
Dura Line	Ronald		Hendriks
Eurofiber	Jeroen		Kanselaar
Genexis	Olivier	van	Duuren
Glaspoort	Heleen		Lamers
Maunt	Maarten		Verbunt
Netways Europe	Luc		Niggebrugge
NLconnect	Mathieu		Andriessen
Odido	Christina		Rieke
Prysmian Group	Frank		Middel
TKF	Henk		Woldhuis
TriNed	Paul	van	Wanrooij

LCA consultants: NIBE BV, Atakan Larcin and Mantijn van Leeuwen.

For further information and contact: info@nlconnect.org

¹ Available from the website [www.milieudatabase.nl](https://milieudatabase.nl). Document is originally in Dutch, an English translation is available on the website. <https://milieudatabase.nl/en/downloads/download/135/>

1 Scope

This document provides general Product Category Rules (PCR) for Type III environmental declarations for passive fiber optical network components for communication services, this includes components such as cables, duct systems, handholes, racks and shelves, closures and wall boxes, patch cords and pigtails and optical fiber connectors. This PCR intends to cover all passive components from point of light signal entry to point of light signal delivery of the optical fiber network². The PoP is not covered by this PCR. Typically the PoP is a prefabricated concrete or steel construction and these are covered by other PCR's.

Environmental declarations are used to assess the environmental performance of construction works. Another function of environmental declarations is to assess the environmental performance of products in purchasing or contracting.

This standard is intended to be used in conjunction with the Dutch standard “Bepalingsmethode milieuprestatie bouwwerken 1.2” (provided by Stichting Nationale Milieudatabase through their website www.milieudatabase.nl). The Bepalingsmethode complements the core rules for the product category of construction products as defined in EN 15804 and is intended to be used in conjunction with EN 15804. Compliance with the Bepalingsmethode will ensure that the environmental declarations can be used in the Dutch context and ensure the required uniformity.

2 Normative references

The following documents, in whole or in part, are referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. In the body of the text of this PCR reference may be made to the standard number (undated), but the specific dated reference as given below applies.

- EN ISO 14025:2010, Environmental labels and declarations — Type III environmental declarations — Principles and procedures
- EN ISO 14044:2006, Environmental management — Life cycle assessment — Requirements and guidelines
- EN 15804+A2:2019, Sustainability of construction works — Environmental product declarations — Core rules for the product category of construction products
- Bepalingsmethode Milieuprestatie bouwwerken v1.2

3 Terms and definitions

For the purposes of this document, the terms and definitions given in The Bepalingsmethode and EN 15084:2019 apply in order of priority (e.g. Bepalingsmethode comes first in case of any conflict in terms and definitions)

4 Abbreviations

MTBF Mean time between failures

² Transformation from light signal to electronic signal takes place in active components of the optical fiber network. Active components are covered in a separate PCR (ref). Active components are network components that consume energy (electricity).

CPE customer Premises equipment

PoP Point of Presence

5 General Aspects

5.1 Objective of this general PCR for optical fiber products for communication services

Bepalingsmethode applies

. The target group of the EPD is primarily the customers using the product.

5.2 Types of EPD with respect to life cycle stages covered

Bepalingsmethode applies³

5.3 Comparability of EPD for construction products

Bepalingsmethode applies

5.4 Additional information

Bepalingsmethode applies

5.5 Ownership, responsibility and liability for the EPD

Bepalingsmethode applies

5.6 Communication format

Bepalingsmethode applies

³ The Bepalingsmethode numbering of the chapters and paragraphs differs in the sense that all chapters of the EN 15804 are part of chapter 2 of the Bepalingsmethode. E.g. paragraph 5.1 of the EN 15804 is 2.5.1. in the Bepalingsmethode

6 Product Category Rules for LCA

6.1 Product category

Bepalingsmethode applies

6.2 Life cycle stages and their information modules to be included

6.2.1 General

Bepalingsmethode applies

6.2.2 A1-A3, Production stage

Bepalingsmethode applies

Optical fiber cables are placed in the ground for a significant time period. Care is needed to avoid that harmful chemicals are leached to the ground or groundwater. To provide transparency the producers will declare any use of substances that are listed in the "Candidate List of Substances of Very High Concern for authorization" when their content exceeds the limits for registration with the European Chemicals Agency. This declaration will be part of general information in the EPD.

NOTE: Often components of products are purchased ready made from third parties. In that case the transportation of the raw materials to the production location may not be known specifically. The use of "market for" processes from Ecolnvent is required in such cases.

6.2.3 A4-A5, Construction process stage

Bepalingsmethode applies

For installation of the optical cable a default scenario is provided as follows⁴:

Trench Excavation

A trench of 30 cm by 70 cm will be excavated with the use of a small digger (1,5-2 ton digger). Due to obstacles in the urban area speed of excavation is limited and ranges from 30 to 120 meter per day. As an average we use 100 meter per day in the default scenario. Estimated use of 5 hours of the 1,5-2 ton digger for excavation of 100 meters is assumed. A 1,5-2 ton digger has a diesel consumption of 10 liter per hour. Thus total diesel consumption is 50 liter for excavation of 100 meter, thus 0,5 liter per meter installed. As part of the excavation work excess amount of excavated soil needs to be transported for further use elsewhere. On average 1 m³ of soil needs to be transported⁵ (per kilometer of placed cable) on average over a distance of 15 kilometer. With a density of 2.000 kg/m³ for soil, this equals a transport scenario of 30 t.km transport. This should be added to the excavation scenario. The excavation scenario of the trench is allocated to the duct system, in case of blowing in application. In case an EPD is published for cables for direct placement (without ducts) the excavation scenario should be applied to the cable.

Replacement of street work

After the trench has been closed the street work is placed back, for this an energy consumption of 0,05 liter of diesel is

⁴ Installation processes depend on the type of underground. For the default scenario typical Dutch urban installation conditions are assumed.

⁵ This amount may be used as estimation. If exact quantity can be calculated from cable volume that may also be used.

assumed per m of duct system. In case an EPD is published for cables for direct placement the scenario should be applied to the cable.

Blowing in of cable

Blowing in of cable is done with a compressor fueled by diesel. Consumption is assumed to be 1.6 liter per hour and 100 m of cable blown in per hour. Diesel consumption of 0,016 liter per meter of cable.

In case of placement in a building instead of underground only the “blowing in of cable” should be applied and not the trench excavation and replacement of street work.

Other activities are carried out with manual labor and do not require energy.

Available environmental profiles from the National Environmental database for diesel or other fuels may be applied, as well as available profiles for different stages for the applied equipment (e.g. IIIB, IV or V). When available also supplier data in the form of an EPD may be applied. In case none of these are available, the Bepalingsmethode applies and background data from the specified version of ecoinvent shall be applied.

This default scenario may be applied. When specific data are available, e.g. for a specific project or for a specific type of installation, these may be applied instead. Adequate numerical substantiation should be provided in this case.

For waste during construction 15 w% shall be used as default scenario for cables. This is a worst case assumption. When specific information is available this may be used, but adequate numerical substantiation shall be provided in the LCA background report.

For other components than cables 3 w% construction waste⁶ shall be used as default scenario, as stated in the Bepalingsmethode. When specific information is available this may be used, but adequate substantiation shall be provided in the LCA background report.

6.2.4 B1-B5, use stage

Bepalingsmethode applies

Duct systems or directly placed, cables are assumed to leach a negligible amount of substances to the ground or ground water. Although not exactly known they are considered to be well below the cut-off criteria and may be omitted.

6.2.5 B6-B7, use stage, related to the operation of the building

Bepalingsmethode applies⁷

⁶ The products are considered prefabricated products and thus the Bepalingsmethode provides a default scenario of 3 w% construction waste

⁷ During use there is a certain amount of signal loss in the network and to compensate for this attenuators are used in the network, depending on the exact local conditions and network design. The attenuators are installed in the PoP. The PoP itself is not covered by this PCR. The operational energy use of the POP is in the Bepalingsmethode not considered to be part of the product EPD or product entry in the central database. The amount of energy needed for attenuation has been estimated using the PSR of the PEP program and was found to be 0,21% of the environmental impact of an optical fiber cable.

6.2.6 C1-C4, End-of-life stage

Bepalingsmethode applies

It is assumed that components of the fiber optical network that are installed underground will stay in the ground after decommissioning of the network. For components that are above ground it is assumed that these will be collected and recycled according to the industry standards. For Cables it is assumed that they will stay in the ground⁸. The Bepalingsmethode provides adequate default scenarios for end of life for the commonly used materials.

6.2.7 D, Benefits and loads beyond the system boundary

Bepalingsmethode applies

6.3 Calculation rules for the LCA

Bepalingsmethode applies

6.3.1 Functional or declared unit

Bepalingsmethode applies

6.3.2 Functional unit

Bepalingsmethode applies

The functional units provided in table 1 shall be used.

Component	Functional unit	Reference service life
Cables	Meter	25 years
Connectivity	piece	25 years
Ductsystem	Meter	25 years
Handholes	piece	25 years
Racks and shelves	piece	25 years
Closures and wall boxes	piece	25 years
Patch cords and pigtails	piece	25 years

Table 1. Functional unit and RLS guidance for optical fiber network components.

In the working group is considered that 25 years is often required as reference service life for underground networks and in our expert opinion can be delivered by current technology.

⁸ In case an EPD is made for a Cable system that is not intended for underground installation, but for instance in buildings another end of life scenario would be appropriate.

NOTE: This PCR covers a wide range of different products all used in fiber optic networks. In the light of the broad range of products it has been chosen to not individually describe the functional unit requirements and typical performance indicators for each of the products that are covered. This PCR can be seen as starting points for harmonization of rules for conducting LCA and declaring EPD's and in a later stage could well be extended to cover the products in more detail.

6.3.3 Declared unit

Bepalingsmethode applies

6.3.4 Reference Service Life (RSL)

Bepalingsmethode applies

NOTE: in the Bepalingsmethode reference is made to a Dutch guide for RSL of buildingproducts (SBS Levensdurengids), this document does not contain any relevant information for the products covered by this PCR.

The RSL provided in table 1 shall be used.

6.3.5 System boundaries

Bepalingsmethode applies

6.3.6 Criteria for the exclusion of inputs and outputs

Bepalingsmethode applies

6.3.7 Selection of data

Bepalingsmethode applies

6.3.8 Data quality

Bepalingsmethode applies

6.3.9 Developing product level scenarios

Bepalingsmethode applies

6.3.10 Units

Bepalingsmethode applies

6.4 Inventory Analysis

6.4.1 Data collection

Bepalingsmethode applies

6.4.2 Calculation procedures

Bepalingsmethode applies

6.4.3 Allocation of input flows and output emissions

Bepalingsmethode applies

6.5 Impact assessment

Bepalingsmethode applies

6.6 Interpretation

Bepalingsmethode applies

7 Content of the EPD

7.1 Declaration of general information

Bepalingsmethode applies

7.2 Declaration of environmental parameters derived from LCA

7.2.1 General

Bepalingsmethode applies

7.2.2 Rules for declaring LCA information per module

Bepalingsmethode applies

7.2.3 Indicators describing environmental impacts based on LCA Assessment

Bepalingsmethode applies

7.2.4 Indicators describing resource use and environmental information based on Life Cycle Inventory (LCI)

Bepalingsmethode applies

7.2.5 Information on biogenic carbon content

Bepalingsmethode applies

7.3 Scenarios and additional technical information

7.3.1 General

Bepalingsmethode applies

7.3.2 Construction process stage

Bepalingsmethode applies

7.3.3 B1-B7 use stage

Bepalingsmethode applies

7.3.4 End-of-life

Bepalingsmethode applies

7.4 Additional information on release of dangerous substances to indoor air, soil and water during the use stage

7.4.1 Indoor air

Bepalingsmethode applies

7.4.2 Soil and water

Bepalingsmethode applies

7.5 Aggregation of information modules

Bepalingsmethode applies

8 Project report

8.1 General

Bepalingsmethode applies

8.2 LCA related elements

Bepalingsmethode applies

8.3 Documentation and additional information

Bepalingsmethode applies

8.4 Data availability for verification

Bepalingsmethode applies

9 Verification and validity of an EPD

Bepalingsmethode applies

10 Bibliography

Bepalingsmethode applies. Additional references:

1. Bepalingsmethode milieuprestatie bouwwerken 1.2, Stichting Nationale milieudatabase, document can be downloaded from www.milieudatabase.nl

2. Carbon performance in the cable industry, Methodologies to assess the Carbon Footprint of organizations and products, Europacable HSE Task Force CARBON FOOTPRINT, Brussels September 2019, Europacable.
3. PSR of PEPECopassport Program, specific rules for Wires, Cables and accessories, PSR-0001-ed4-EN-2022 11 16, 2022 Association P.E.P.